



# Cat<sup>®</sup> Contractors' Grapples

## G100 Models

***Cat<sup>®</sup> Contractors' Grapples are a proven product built for your high-volume material handling needs. Designed for long-lasting durability, Contractors' Grapples are made to help you in the toughest of applications.***

***Not all attachments are available in all regions. Consult your Cat dealer for specific attachments available in your region.***

### **Strong and Durable**

- Wide surface area for demolition and material handling applications with a rigid, box-type design.
- Penetrate, securely grasp, and retain materials better with two-over-three interlocking tines.
- Keep an eye on your work with long, wide-spaced tines for better visibility.
- Tips, wrapper, and wear strips are made of AR400 steel for long-lasting durability in the harshest applications.

### **Increase Productivity**

- Debris loads and unloads seamlessly without catching due to the tips mounted flush with the wrapper.
- Optimize material flow and penetration into piles with less curvature in the lower jaw.
- Maintain high-volume production when using the grapple pinned to the machine or with a Pin Grabber Coupler.
- Purpose-designed to match their respective machine sizes for maximum performance in break out and lift capacity.
- Share your grapple across similar-sized excavators for maximum utilization with the use of replaceable pins to match different linkages.
- Capacities calculated according to SAE J2754, an industry-leading standard for fabricated grapples.
- Optimal for applications such as: structural demolition, material handling and sorting, and loading and unloading rock, scrap, pipe, waste material, and other debris.

### **Easy to Maintain**

- No need for added hydraulics or hoses. Contractors' Grapples utilize the bucket linkages for operation.
- Long-lasting, field-serviceable tips have extended service life without extra weight.
- Jaws stay connected when the grapple pin is removed with the advanced modular pin hub system.
- Field-install an extreme duty wear package for extra protection on your grapple.



# Cat® G100 Contractors' Grapples

Specifications										
Model	Part Number	Linkage	Weight		Maximum Jaw Opening		Jaw Minimum		Wear Tip Thickness	
			kg	lb	mm	in	mm	in	mm	in
G113	590-1850	312	857	1885	2195	86.40	186	7.30	20	0.80
G117	590-1855	315	1286	2830	2555	100.60	191	7.50	25	1.00
G120	590-1856	B	1523	3350	2687	105.80	199	7.80	30	1.20
G126	590-1859	B	1932	4250	3128	123.10	246	9.60	40	1.60
G120	590-1858	CB	1523	3350	2687	105.80	199	7.80	30	1.20
G126	590-1862	CB	1932	4250	3128	123.10	246	9.60	40	1.60
G136	590-1864	CB	2332	5130	3223	126.90	319	12.60	40	1.60
G136	590-1867	DB	2332	5130	3223	126.90	319	12.60	40	1.60
G149	590-1869	TB	3050	6724	3433	135.20	271	10.70	40	1.60
G174	590-1871	VB	4055	8940	3860	152.00	283	11.10	40	1.60

GEHQ2287-00 (05-2020)  
(N Am, S Am)

